





Lens Point

# LENS POINT (INDIA) PVT. LTD.

## 60°

## Flood Light Lens




PART NUMBER	SIZE	LED MATERIAL	LED PACKAGE	LED MANUFACTURER
LP20_8X1_5050_60°-50509.1_FL3	50X50X9.1 mm	PC	5050	OSRAM LUMILEDS CREE SEOUL bridgelux

### General Information

- Lens Material : Optical Grade PC (Bayer 2407)
- Luminous transmittance : 89 to 90%(ISO 135468-/ASTM D1003)
- Refractive index : 1.584 (ISO 489/ASTM D542)
- Operating Temperature range -40°C to 110°C (upper limit +130°C)
- Flammability : HB/V-o (UI94)
- If necessary, clean lenses with mild soap, water and soft cloth.
- Never use any commercial cleaning solvents on lenses, like alcohol
- Please handle or install lenses with wearing gloves, skin oils may damage lens or its optical characteristics.




### Application




Plot No.3, Kaili Industrial Area, Main GT Road, Ballabgarh, Faridabad-121004, Haryana

+91 9711472021, 7838461601

lenspointindia@gmail.com www.lenspointindia.com



ALL DIMENSIONS IN MM



# LENS POINT (INDIA) PVT. LTD.

FIRST ISSUED	07-03-2022
DRAWN BY	AJAY BIDHRUI
CHECKED BY	AKASH
APPROVED BY	VISHAL MITTAL
MATERIAL	PC

TITLE	
8X1 FL LENS WITH SHRINKAGE 0.45%	
SIZE	DRG NAME
A4	LPFL-8X1_5050
SHEET REV	
A	

SCALE 1:1 SHEET 1 OF 1